


# Direct drive gear pump-motor units DGD PRO

The Fluid-o-Tech® DGD PRO direct drive gear pump has an AISI 316L stainless steel housing and Peek gears. The ports are 1/8" GAS in line. Designed to extend the performance of the DGD series pumps in both flow rate and pressure, the DGD PRO pump-motor unit is built to handle food grade liquids in compliance with the most stringent standards.

The DGD PRO delivers great performances in a small footprint and it is available with brush and brushless drives to cover the widest range of applications and requirements.




## MAIN APPLICATIONS


- Food equipment
- Lubrication
- Fluid transfer
- Water treatment
- Sanitization



## TECHNICAL INFORMATION

Pump housing material	AISI 316L	Nominal speed	2800 rpm
Gears and bushing material	Peek	Max output power	50 W
Ports	1/8" GAS	Motor IP protection	IP 30
Max static pressure	10 bar/145 psi	Insulation class	B
Motor type	24 V Brush	Unit weight	830 g/1.8 lb





Fluid-o-Tech reserves the right to alter the specifications indicated in this catalogue at any time and without prior notice.

**Fluid-o-Tech srl**  
 Via Leonardo da Vinci, 40  
 20094 Corsico, Milano, Italy  
 Tel. +39 02 9995 01  
 Fax +39 02 9995 0999  
 info@fluidotech.it

**Fluid-o-Tech Int'l Inc.**  
 161 Atwater St.,  
 06479 Plantsville CT (USA)  
 Tel. +1 (860) 276 9270  
 Fax +1 (860) 620 0193  
 info@fluid-o-tech.com

**Fluid-o-Tech Int'l Inc. Japan**  
 2nd Floor, 4-3-8, Espoir Todoroki,  
 Todoroki, Setagaya, Tokyo 158-0082  
 Tel. +81 (0) (3) 6432 1812  
 Fax +81 (0) (3) 6432 1813  
 erkkato@fluidotech.jp

**Fluid-o-Tech Asia (Shanghai) Co., Ltd.**  
 2/F, Factory building 6 (1), No. 258, Zhijiang Road,  
 Fengxian District, Shanghai City, Z.P.: 201499 China  
 Tel. +86 (021) 67100 838  
 Fax +86 (021) 67100 605  
 info@fluidotech-asia.com