

Magnet drive rotary vane pump-motor units PMFR series

The PMFR series pump-motor unit represents a significant step forward. Small, light-weighted and based on the patented T2 Coil motor design, the PMFR is electromagnetically driven, with no moving parts in the motor and a completely resin encapsulated coil with IP54 rating.

Thanks to the pump housing in PPS, the PMFR complies with the most stringent regulatory limits in terms of release of substances in the water used for human consumption.

The seal-less design contributes to reduce the power consumption thanks to the lower friction, prevents any potential misalignment between the pump and the motor and significantly reduces the risk of leaks. The ports with quick-disconnect system make the removal of the unit for servicing simple.




MAIN APPLICATIONS

- Espresso coffee machines
- Beverage dispensing machines
- Cooling systems



TECHNICAL INFORMATION

Pump housing material	PPS	Speed	3000 rpm
Pumping chamber	Carbon graphite	Max static pressure	10 bar/145 psi
Ports	Quick connections Øi 14.5	Unit weight	1.9 Kg (4.2 lb)




Dimensions in mm [inches]

MOTOR CHARACTERISTICS

Motor type	Single phase synchronous motor with double insulation	Insulation class	F
Motor power	100 W	Thermal protection interlock	130 °C
Voltage-frequency	230V AC - 50 Hz	Cable type	Multi-pole, insulated
Connector type	Faston 6.3 x 0.8	Capacitor type	Class A 420V

PMFR @ 3000 rpm

Flow rate
[GPH - l/h]



Note: Hydraulic characteristics with water at 20 °C (68 F) and with bypass closed. Use filter before pump inlet not larger than 10 microns.
For applications involving other fluids, high temperatures or unusual processing conditions, please consult the factory or an authorized Fluid-o-Tech distributor.

Fluid-o-Tech reserves the right to alter the specifications indicated in this catalogue at any time and without prior notice.

Fluid-o-Tech srl
Via Leonardo da Vinci, 40
20094 Corsico, Milano, Italy
Tel. +39 02 9995 01
Fax +39 02 9995 0999
info@fluidotech.it

Fluid-o-Tech Int'l Inc.
161 Atwater St.,
06479 Plantsville CT (USA)
Tel. +1 (860) 276 9270
Fax +1 (860) 620 0193
info@fluid-o-tech.com

Fluid-o-Tech Int'l Inc. Japan
201, 4-3-10, Todoroki,
Setagaya, Tokyo 158-082, Japan
Tel. +81 (0) (3) 6432 1812
Fax +81 (0) (3) 6432 1813
erkkato@fluidotech.jp

Fluid-o-Tech Asia (Shanghai) Co., Ltd.
2/F, Factory building 6 (1), No. 258, Zhijiang Road,
Fengxian District, Shanghai City, Z.P.: 201499 China
Tel. +86 (021) 67100 838
Fax +86 (021) 67100 605
info@fluidotech-asia.com